



Technical Specification

FOCUS AW HYDRAULIC 68

Product Description:

Extremely high quality hydraulic oil developed for extensive range of heavy duty hydraulic operations with anti-wear and anti-oxidation properties. FOCUS AW HYDRAULIC 68 is designed to provide substantial cost savings to maintenance cost as well as promote equipment availability due to supreme equipment protection and long filter life.

Benefits:

- *Enhanced temperature stability*
- *Anti-wear*
- *Protects against rust and corrosion*
- *Very low foaming*

Typical Characteristics:

Item	Characteristics	Test Method ASTM D
Appearance	Bright and Clear	Visual
Colour	L1.5	1500
Density @30 degrees C	0.873	4052
Kinematic Viscosity @ 40 degrees C	69.10	445
Kinematic Viscosity @ 100 degrees C	8.937	445
Viscosity Index	106	2270
Flash Point	222 degrees C	92
Pour Point	Minus 21 degrees C	97

Figures given are typical of current production and conform to specification. May be subjected to minor variation.
FOCUS SOLUTIONS PTE. LTD.
Co. Registration Number: 201206049W

Email: info@focus-sol.com



Exceeds the following specifications and approvals:

- DIN 51524, PART 2 (HLP), (HLP ISO VG 68)
- AFNOR NF E 48-603 (HM)
- Denison T-6H20C Hybrid Pump
- Denison HF-0,
- Denison HF-1,
- Denison HF-2
- Cincinnati Machine P-68
- Cincinnati Machine P-69
- Cincinnati Machine P-70
- Vickers M-2950-S
- U.S. Steel 127, 136
- FZG A/8.3/90 Load test (DIN 51354) at 12th stage level

